



VENEER STRIPING INK

Product Information

PRODUCT DESCRIPTION

Willamette Valley Company has formulated bright legible inks for masking plywood, veneer and other wood products in the industry. Veneer Striping Ink Concentrate (VIC) comes in almost every color and is intended for all veneer striping. VIC Inks come in concentrated form - 50 to 1 dilution.

PHYSICAL CHARACTERISTICS

Solids: N/A
Wt/Gal: 8.34
Viscosity: N/A
Colors: Available in most colors
pH: 7.5 - 7.8
Shelf Life: 9 months (May require agitation)
Freeze Thaw Stability: Good (Will require agitation)
Storage: Store out of direct sunlight. Extreme heat will cause ink to break down.
Store between 38°F to 100°F.

APPLICATION

In order to use Veneer Striping Ink effectively in the detection system, the lines must first be flushed with water. This will assure you that incompatibility with old product does not take place. VIC can be applied with Sure Shot Moisture Meter or any other industrial spray applicator. VIC inks are based on a specific 50 to 1 ratio. Mixing improperly may inhibit performance. VIC is intended for in-house use and will fade in time when subjected to direct sunlight.

PERFORMANCE TESTING

In its intended application VIC Ink exhibits good color strength, but can fade to varying degrees after 3 or more months. Willamette Valley Company has tested their inks thoroughly and believes them to be the best possible inks for their intended use.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Collect as much as practical with scoop or shovel. If feasible absorb with an inert substance before collecting. Mop up residue with water, then mop again with 1 to 1 solution of chlorine bleach and water. Ink will stain skin and clothing. Use waterless hand cleaner then wash with soap and water.

HAZARDS

When handling this product in its concentrated form it is recommended that Neoprene gloves, rubber or plastic apron, and chemical splash goggles or full face shield be worn. In its diluted, ready-to-use form this product exhibits minimal risks in the work place.

Willamette
Valley Company
660 McKinley Street
P.O. Box 2280
Eugene, OR 97402
☎ 541 484-9621
FAX 541 484-1987

Consult the MATERIAL SAFETY DATA SHEET before using this product.